

TABLETOP CHAMBERS

CAMPANE DA BANCO

CAMPANAS DE SOBREMESA

PROFESSIONAL Plus



20 PROGRAMS
PROGRAMMI
PROGRAMAS

- **SOFT VACUUM**
- **MARINATING FUNCTION**
- **VACUUM SENSOR**



AUSTER +



EOS +



LEVANT +



MISTRAL +



GHIBLI +

Machine dimensions Dimensioni macchina Dimensiones máquina	380 x 475 x 390h mm	445 x 455 x 460h mm	510 x 560 x 520h mm	560 x 560 x 520h mm	660 x 670 x 520h mm
Weight Peso Peso	28 kg	36 kg	39 kg	60 ^A kg / 62 ^B kg	78 ^A kg / 78 ^B kg
Voltage Voltaggio Voltaje	110 V-60 Hz ● 230 V-50/60 Hz	110 V-60 Hz ● 230 V-50/60 Hz	110 V-60 Hz ● 230 V-50/60 Hz	110 V-60 Hz ● 230 V-50/60 Hz	110 V-60 Hz ● 230 V-50/60 Hz
Consumption Consumo Consumo	0,45 kW	0,45 kW	0,55 kW	0,55 ^A kW 0,90 ^B kW	0,90 ^A kW 0,90 ^B kW
Chamber dimensions Dimensioni camera Dimensiones cámara	270 x 350 x 190h mm	330 x 330 x 215h mm	370 x 440 x 215h mm	430 x 430 x 220h mm	530 x 530 x 235h mm
Oil lubricated pump Pompa a bagno d'olio Bomba de baño de aceite	8 m3/h Busch®	8 m3/h Busch®	16 m3/h Busch®	16 ^A /21 ^B m3/h Busch®	21 ^A /25 ^B m3/h Busch®
Welding bar Barra saldante Barra de soldadura	260 mm	320 mm	365 mm	420 mm ● 420/420 mm	520 mm ● 520/520 mm
Second welding bar (opt.) Seconda barra saldante (opz.) Segunda barra de soldadura (opc.)	×	×	×	✓	✓
Cut-off seal bar (opt.) ● Barra taglio sfrido (opz.) Barra con corte de bolsa (opc.)	✓	✓	✓	✓	✓
Double seal bar (opt.) ● Barra doppia saldatura (opz.) Barra doble soldadura (opc.)	✓	✓	✓	✓	✓
Protective atmosphere (opt.) Atmosfera protettiva (opz.) Atmósfera protegida (opc.)	✓	✓	✓	✓	✓
Vacuum sensor ● Sensore di vuoto Sensor de vacío	Incl.	Incl.	Incl.	Incl.	Incl.
Marinating function ● Funzione marinatura Funcion marinado	Incl.	Incl.	Incl.	Incl.	Incl.
Liquids inclined shelf (acc.) Piano inclinato per liquidi (acc.) Estante inclinado para líquidos (acc.)	✓	✓	✓	✓	✓
Printer (opt.) Stampante (opz.) Impresora (opc.)	×	×	✓	✓	✓
Soft air (opt.) Soft air (opz.) Soft air (opc.)	✓	✓	✓	✓	✓
Vacuum gauge Vuotometro Vacuometro	Incl.	Incl.	Incl.	Incl.	Incl.
Vacuum in GN pans prearrangement Predisposizione vuoto teglie GN Predisposición vacío en bandejas GN	Incl.	Incl.	Incl.	Incl.	Incl.
WiFi module for remote diagnostics Scheda WiFi Compatibilità Industry 4.0 Módulo WiFi para diagnóstico a distancia	4.0 ×	×	●	●	●

● Special voltage on demand
● Non-cumulative options
● Standard

Voltaggio speciale su richiesta
Opzioni non cumulabili
Di serie

Voltaje especial a petición
Opciones no acumulativas
Estándar