
HX10


- Inverter technology
- Make steps simple
- Optimize the transmission structure
- Ergonomic A.I. Technology












HX10A control panel



HX10B control panel

Model	Head	Transmission	Bowl Capacity(L)	Speed	Maximum Kneading Capacity(kg)	Minimum Flour(kg)	Maximum Flour(kg)	Motor Power(kw)	Voltage(V)	Agitator speeds(RPM)	Dimensions(mm) A B C	Net Weight(kg)
HX10A	Fixed Head	VFD+Belt	10	4	5.25	0.25	3.5	0.75	220	108-272	550*320*440	32
HX10B	Fixed Head	VFD+Belt	10	10	5.25	0.25	3.5	0.75	220	108-272	550*320*440	32

HX10T


- Flour Dust Protection
- Simple Hand Lock System
- Bowl Protection
- Hand Safety Protection
- Bowl Lock Improvement














Model	Head	Transmission	Bowl Capacity(L)	Speed	Maximum Kneading Capacity(kg)	Minimum Flour(kg)	Maximum Flour(kg)	Motor Power(kw)	Voltage(V)	Agitator speeds(RPM)	Dimensions(mm) A B C	Net Weight(kg)
HX10T	Lifted Head	VFD+Belt	10	10	5.25	0.25	4	0.75	230	108-272	593*324*434	41