


Glo-Max ®
Curved Infrared Strip Heaters

Models

GM5AH	-24/-30/-36/-42/-48/-54/-60/-66/-72/-78
GM5AHL	-24/-30/-36/-42/-48/-54/-60/-66/-72/-78

This stylish design, based on our Glo-Max strip heaters, is the perfect solution for your front-of the-house applications. Superb for buffet and serving lines, the sleek curved design minimizes its size while accenting and warming the products below.

GM5AHL, with versatile LED lighting options, provides perfect coloring and coverage while lowering energy costs.



Features

- The entire holding surface is heated evenly with no “cold"spots, thanks to Hatco's dependable infrared element technology
- 10 lengths are available:610,762,915,1067,1219,1372,1524,1677,1829,1982 mm (24"~78")
- GM5AHL has energy efficient dual LED lights across the entire strip heater which provides longer performance and energy savings (compared to standard incandescent bulbs)
- Remote box with switches control lights and heat separately
- Accessory: Sneeze-guard mounting kit
- Angle brackets are standard, non-adjustable tubular stands are an option
- GM5AHL has LED lights, GM5AH has no lights




With sneeze guard mounting kit accessory
Sneeze guard not included


GLO-MAX®

Curved Infrared Strip Heaters


Models: GM5AH/GM5AHL

Unit: mm





Control Box Cutout and Screw Hole Dimensions



● Specification

Model	Voltage	Watts	Amps	Weight	Model	Voltage	Watts	Amps	Weight	Dimensions(A Models) WxDxH
GM5AH-24	220 ~ 230	500	2.3 ~ 2.4	5kg (10lbs)	GM5AHL-24	220 ~ 230	510	2.3 ~ 2.4	5kg (12lbs)	24" x 6" x 2" (610 x 150 x 51 mm)
GM5AH-30		660	3.0 ~ 3.1	5kg (11lbs)	GM5AHL-30		670	3.0 ~ 3.2	6kg (14lbs)	30" x 6" x 2" (762 x 150 x 51 mm)
GM5AH-36		800	3.6 ~ 3.8	6kg (14lbs)	GM5AHL-36		812	3.7 ~ 3.9	7kg (14lbs)	36" x 6" x 2" (915 x 150 x 51 mm)
GM5AH-42		950	4.3 ~ 4.5	7kg (15lbs)	GM5AHL-42		964	4.4 ~ 4.6	7kg (15lbs)	42" x 6" x 2" (1067 x 150 x 51 mm)
GM5AH-48		1010	4.4 ~ 5.2	7kg (16lbs)	GM5AHL-48		1116	4.5 ~ 5.3	8kg (17lbs)	48" x 6" x 2" (1219 x 150 x 51 mm)
GM5AH-54		1250	5.7 ~ 5.9	8kg (18lbs)	GM5AHL-54		1260	5.8 ~ 6.0	9kg (18lbs)	54" x 6" x 2" (1372 x 150 x 51 mm)
GM5AH-60		1400	6.4 ~ 6.7	8kg (18lbs)	GM5AHL-60		1418	6.4 ~ 6.7	9kg (20lbs)	60" x 6" x 2" (1524 x 150 x 51 mm)
GM5AH-66		1560	7.1 ~ 7.4	9kg (20lbs)	GM5AHL-66		1579	7.2 ~ 7.5	10kg (22lbs)	66" x 6" x 2" (1675 x 150 x 51 mm)
GM5AH-72		1725	7.8 ~ 8.2	10kg (21lbs)	GM5AHL-72		1744	7.9 ~ 8.3	10kg (22lbs)	72" x 6" x 2" (1829 x 150 x 51 mm)
GM5AH-78		1890	8.6 ~ 9.0	10kg (22lbs)	GM5AHL-78		1910	8.7 ~ 9.1	11kg (24lbs)	78" x 6" x 2" (1981 x 150 x 51 mm)

* Housing color : clear anodized
* Accessory: Sneeze-guard mounting kit
* Angle brackets are standard, non-adjustable tubular stands, 409 mm (16"), are an option*Warm LED light(3000K)
* Power wire lead length is 1524 mm (60")
* Plugs: CCC,Schuko, BS or AU

2024.01